



HOP AIR

FUNCTIONAL CHARACTERISTICS

Display	DIGITAL
Supply	ELECTRIC
Timer	-
Number of motors	1
Motor speeds	1
Max cooking temperature (°C)	260°C
Core probe	-
Cooking chamber material	AISI 304
Opening door	FROM RIGHT TO LEFT

STANDARDS

Certification	CE
---------------	----

TRAYS	
Trays rack	BASKET
Max tray load	3kg
DIMENSIONS	
Oven size with handle WxDxH (mm)	701 x 783 x 549
Oven size without handle WxDxH (mm)	701 x 723 x 549
Chamber size WxDxH (mm)	454 x 304 x 305
Unit weight (Kg)	44
PACKAGING	
Packaging	PALLET + PAPER BOARD
Packaging size WxDxH (mm)	750 x 950 x 606
Unit weight with packaging (Kg)	67
Crate packaging size (optional)	-
ELECTRICAL DATA	
Heaters 4,5kW 50/60Hz	
Power	3,4kW
Frequency	50/60Hz
Power supply	220-240V ~
Amperage	14,8A
Power cord req.	3G1,5
WATER CONNECTION REQUIREMENTS	
Humidification Water inlet	-
Washing Water inlet	-
Water drain	YES
Max water hardness	5°f
Water pressure requirement min-max	-
CONSUMPTION	
Humidification Water	-
Rinse Water @2barG	-
Short Washing Water @2barG	-
Long Washing Water @2barG	-
Short Washing Detergent *	-
Long Washing Detergent *	-

CONNECTIVITY

USB	2.0
Bluetooth	-
Wi-Fi	-
Cloud	-

ACCESSORIES

Self clean system kit	-
Oven stand	T7
Wheels kit for stand	R60B
Hood (Air)	H7V
Hood (Water)	-
Core probe	-
Proofer	-
Stacking kit for 2 ovens	SK32
Smoker	-
Blast chiller	-
Blast chiller stacking kit	-
Water softner cover	WS10
Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	85KIT00001
Detergent 750ML (for Self clean system or Manual shower kit)	DT1
Detergent 6KG	DT2
Detergent 10KG	DT4

 Innovative Technologies
suisse systems
0800 00 99 99

