



SPZLROFER00
PIZZA KIT INCLUDED

HIGH-SPEED CONVECTION OVEN
2,4" LCD DIGITAL CONTROL

 Innovative Technologies
suisse systems
0800 00 99 99

FUNCTIONAL CHARACTERISTICS

Display	DIGITAL
Supply	ELECTRIC
Timer	-
Number of motors	1
Motor speeds	5 speed + inverter
Max cooking temperature	260 °C
Probe	Single point PT1000
Cooking chamber material	AISI 304
Opening door	Flap door
Chimney	20 mm open
Humidification	-
Air Injection	-
Version	Standard
Ventless	-

STANDARDS

Certification	CE
---------------	----

TRAYS

Trays rack	sheet metal single level
Max tray load	3 Kg

DIMENSIONS

Oven size with handle WxDxH	460 x 655 x 525 mm
Oven size without handle WxDxH	460 x 610 x 525 mm
Chamber size WxDxH	320 x 315 x 215 mm
Unit weight	36 kg

PACKAGING

Packaging	CARTON BOX
Packaging size WxDxH	544 x 694 x 570 mm
Unit weight with packaging	48.4 kg
Crate packaging size (optional)	510 x 720 x 670 mm
Unit weight with crate packaging (optional)	61.8 kg

ELECTRICAL DATA

Heaters 3,1 kW (50/60 Hz)	
Power	3,4kW
Frequency	50/60 Hz
Power supply	220-240V ~
Amperage	14,8A
Power cord req.	3G1,5

WATER CONNECTION REQUIREMENTS

Humidification Water inlet	-
Washing Water inlet	-
Water drain	-
Max water hardness	-
Water pressure requirement min-max	-

CONSUMPTION

Humidification Water with solenoid valve	-
Humidification Water with pump	-
Rinse Water @2barG	-
Short Washing Water @2barG	-
Long Washing Water @2barG	-
Short Washing Detergent *	-
Long Washing Detergent *	-

CONNECTIVITY

USB	USB 2.0
Bluetooth	-
Wi-Fi	STANDARD
Cloud	STANDARD

ACCESSORIES

Pizza paddle	SPZFLLA (1 included)
Panini paddle	SPZSHO
Pizza teflon tray	GRI00327 (1 included)
Panini grill	GRI00310
No-stick cook plate liners 270x270mm	GPP00086
No-stick cook plate liners 305x305mm	GPP00088 (1 included)
Solid no-stick basket	GPP00087 (1 included)
Bottom teflon tray	VAS00080 (1 included)