



## VE043LTHAERO

4 TRAYS 460 X 340 / GN 2/3\*

 Innovative Technologies  
**suisse systems**  
0800 00 99 99

\*Special tray rack support on request

#### FUNCTIONAL CHARACTERISTICS

|                          |                  |
|--------------------------|------------------|
| Display                  | LCD 2,4" IPS     |
| Supply                   | Electric         |
| Timer                    | -                |
| Number of motors         | 1                |
| Motor speeds             | 5                |
| Max cooking temperature  | 260°C            |
| Core probe               | -                |
| Cooking chamber material | AISI 304         |
| Opening door             | Flap Door        |
| Chimney                  | 30mm open        |
| Humidification           | Direct injection |
| Air injection            | -                |
| Self-washing             | -                |

#### STANDARDS

|               |    |
|---------------|----|
| Certification | CE |
|---------------|----|

#### TRAYS

|               |                                                                       |
|---------------|-----------------------------------------------------------------------|
| Trays rack    | 4 x PA WIRE 4/80 (460X340)<br>OPT 4 x GA-BIV 4/80 GN2/3 PA<br>460X340 |
| Max tray load | 4kg                                                                   |

#### DIMENSIONS

|                                     |             |
|-------------------------------------|-------------|
| Oven size with handle WxDxH (mm)    | 600x770x540 |
| Oven size without handle WxDxH (mm) | 600x730x540 |
| Chamber size WxDxH (mm)             | 495x420x345 |
| Unit weight (kg)                    | 50 kg       |

#### PACKAGING

|                                 |                     |
|---------------------------------|---------------------|
| Packaging                       | Pallet + Carton box |
| Packaging size WxDxH (mm)       | 675x825x692         |
| Unit weight with packaging (Kg) | 60 kg               |

#### ELECTRICAL DATA

|                         |         |
|-------------------------|---------|
| HEATERS 3,1kW (50/60Hz) |         |
| Power                   | 3,4kW   |
| Frequency               | 50/60Hz |

|                                      |                                                |
|--------------------------------------|------------------------------------------------|
| Power supply                         | 230V 1~                                        |
| Amperage                             | 15A                                            |
| Power cord req.                      | 3G1,5                                          |
| <b>WATER CONNECTION REQUIREMENTS</b> |                                                |
| Humidification Water inlet           | 3/4" M Gas threaded                            |
| Washing Water inlet                  | 8mm quick fitting                              |
| Water drain                          | -                                              |
| Max water hardness                   | 5°f                                            |
| Water pressure requirement min-max   | 150-200 kPa                                    |
| <b>CONSUMPTION</b>                   |                                                |
| Humidification Water                 | 0-2,4 l/h                                      |
| Rinse Water @2barG                   | -                                              |
| Short Washing Water @2barG           | -                                              |
| Long Washing Water @2barG            | -                                              |
| Short Washing Detergent *            | -                                              |
| Long Washing Detergent *             | -                                              |
| <b>CONNECTIVITY</b>                  |                                                |
| USB                                  | USB 2.0                                        |
| Bluetooth                            | -                                              |
| Wi-Fi                                | Standard                                       |
| Cloud                                | Standard                                       |
| <b>ACCESSORIES</b>                   |                                                |
| Oven stand                           | TA6054H80S-TA6054H80X<br>TA6054H60S-TA6054H60X |
| Wheels kit for stand                 | R100                                           |
| Hood (Air)                           | -                                              |
| Hood (Water)                         | -                                              |
| Core probe                           | -                                              |
| Proofers                             | CA6008M0<br>CA6008MH<br>CA6008DH               |
| Stacking kit for 2 ovens             | SK52                                           |
| Smoker                               | SMK02                                          |
| Blast chiller                        | -                                              |
| Blast chiller stacking kit           | -                                              |



|                        |      |
|------------------------|------|
| Water softner cover    | WS10 |
| Water softner 6800L    | WS11 |
| Water softner 12000L   | WS12 |
| Water pressure adapter | WPA  |
| Water shower kit       | S1   |
| Detergent 6KG          | DT2  |
| Detergent 10KG         | DT4  |

 Innovative Technologies  
***suisse systems***  
**0800 00 99 99**