



## VE04LTDALR0

4 TRAYS 600 X 400 -GN 1/1

 Innovative Technologies  
**suisse systems**  
0800 00 99 99

### FUNCTIONAL CHARACTERISTICS

Display	LCD 2,4" IPS
Supply	Electric
Timer	-
Number of motors	1
Motor speeds	5
Max cooking temperature	260°C
Core probe	-
Cooking chamber material	AISI 304
Opening door	Flap Door
Chimney	30mm open
Humidification	Direct injection
Air injection	V-Dry
Self-washing	-

### STANDARDS

Certification	CE
---------------	----

### TRAYS

Trays rack	4 PA Wire 4/80 4 GA-BIV wire 4/80
Max tray load	4kg

### DIMENSIONS

Oven size with handle WxDxH (mm)	800x840x541
Oven size without handle WxDxH (mm)	800x800x541
Chamber size WxDxH (mm)	695x465x345
Unit weight (kg)	60 kg

### PACKAGING

Packaging	Pallet + Carton Box
Packaging size WxDxH (mm)	885x850x695
Unit weight with packaging (Kg)	70

### ELECTRICAL DATA

HEATERS 6.5kW (50/60Hz)	
Power	6,3kW
Frequency	50/60Hz
Power supply	380-415V 3N~/ 230V 1~



Water softner 6800L	WS11
Water softner 12000L	WS12
Water pressure adapter	WPA
Water shower kit	-
Detergent 6KG	-
Detergent 10KG	-

 Innovative Technologies  
***suisse systems***  
0800 00 99 99

Amperage	10,2A / 27,5A
Power cord req.	5G1 / 3G4
<b>WATER CONNECTION REQUIREMENTS</b>	
Humidification Water inlet	3/4" M Gas threaded
Washing Water inlet	-
Water drain	-
Max water hardness	5°f
Water pressure requirement min-max	150-200 kPa
<b>CONSUMPTION</b>	
Humidification Water	0-2,4 l/h
Rinse Water @2barG	-
Short Washing Water @2barG	-
Long Washing Water @2barG	-
Short Washing Detergent *	-
Long Washing Detergent *	-
<b>CONNECTIVITY</b>	
USB	USB 2.0
Bluetooth	-
Wi-Fi	Standard
Cloud	Standard
<b>ACCESSORIES</b>	
Oven stand	TA8058H60X - TA8058H60S TA8058H80X - TA8058H80S
Wheels kit for stand	R100
Hood (Air)	-
Hood (Water)	-
Core probe	-
Proofers	CA8008M0 CA8008MH CA8008DH
Stacking kit for 2 ovens	SK51
Smoker	SMK02
Blast chiller	-
Blast chiller stacking kit	-
Water softner cover	WS10